



Husqvarna PG 530

PG 530 is a concrete floor grinder available in both 1- and 3-phase versions with high capacity. Its grinding width of 21 in. means it is excellent for residential and light commercial purposes. PG 530 combines the latest technology to deliver more power and performance than any other triple head planetary machine available in its class. Excellent choice for concrete floor preparation and repair as well as all polishing and grinding applications – both wet and dry. Perfect for HiPERFLOOR[®] concrete floor polishing system.

Motor

| | |
|-------------------|-----------|
| Rated input power | 5 hp |
| Rated current | 14 A |
| Voltage | 220-240 V |
| Phases | 1 ph |
| Frequency | 60 Hz |

Dimensions

| | |
|---------------------|----------|
| Product size width | 47.05 in |
| Product size height | 47 in |
| Weight | 440 lbs |

Other

| | |
|--------------------------|---|
| Grinding width | 21 in |
| Grinding disc speed min | 200 rpm |
| Grinding disc speed max | 900 rpm |
| Planetary head speed max | 10-60 rpm |
| Direction of rotation | FWD/REV with grinding discs and planetary head rotation in same direction (not counter rotation). |
| Number of grinding discs | 3 |

Articles for PG 530

| | |
|------------------|--------------|
| Husqvarna PG 530 | 965 19 58-14 |
| Husqvarna PG 530 | 965 19 58-21 |

Features for PG 530

High production rate



High power machinery capable of delivering high production rates, increasing profit and saving valuable time.

Stable operation over undulating surfaces




The triple-headed grinder delivers more downward pressure and power to the grinding heads.

Gear-driven planetary head



Gear-driven planetary head; premium quality belt for powering grinding heads.

Time saving tool change




Redi Lock® is an instant and hassle-free system for changing diamond tooling.

Recommended tools for PG 530




HiperFlex FP40




HiperFlex FP80



HiperFlex FT80




Vari-Grind G 670
Redi Lock



Cap Cutters

| | | | | | |
|----------------------|-------|-------|-------|-------|--|
| Concrete | ● ● ● | | ● ● ● | | |
| Concrete hard | ● ● ● | | | | |
| Concrete medium | ● ● ○ | | ● ● ○ | | |
| Concrete soft | | | ● ● ● | ● ● ● | |
| Marble | | ● ● ● | | | |
| Paint and thin epoxy | ● ● ○ | | | ● ○ ○ | |

| | | | | | |
|----------------------------|-------|-------|-------|-------|-------|
| Plastic-like ceramic glues | ● ● ○ | | | | |
| Porous ceramic glues | | | | ● ● ● | |
| Rain-damaged concrete | | | | ● ● ○ | |
| Semi-polished concrete | | | | | ● ● ● |
| Terrazzo | | ● ● ● | ● ● ● | | |
| Thick epoxy | | | | ● ○ ○ | |
| Vinyl glues | ● ● ● | | | ● ○ ○ | |



Arrow Redi Lock



Copper Transitional Pads



Transition Post Pads



CP 1200 series



P 1100 range

| | | | | | |
|----------------------------|-------|-------|-------|-------|-------|
| Concrete | | ● ● ● | ● ● ● | | |
| Concrete hard | | | | ● ● ○ | ● ● ○ |
| Concrete medium | | | | ● ● ● | ● ● ● |
| Concrete soft | | | | ● ● ○ | ● ● ○ |
| Paint and thin epoxy | ● ● ● | | | | |
| Plastic-like ceramic glues | ● ● ● | | | | |
| Porous ceramic glues | ● ● ● | | | | |
| Thick epoxy | ● ● ● | | | | |
| Vinyl glues | ● ● ● | | | | |



P 1200 series for PG machines

| | |
|-----------------|-------|
| Concrete hard | ● ● ○ |
| Concrete medium | ● ● ● |
| Concrete soft | ● ● ○ |
| Terrazzo | ● ○ ○ |