



5280

WALK-BEHIND SCRAPER

5280-AUS, 5280-EUR, 5280-UK, 5280-HER, 5280-INT, 5280-KTU



This hydraulically driven, forward self-propelled scraper removes the worst of today's soft goods, such as glued-down floors, gummy commercial carpet, VCT, sheet vinyl, rubber tile, linoleum, indoor and outdoor sport surfaces, roofing material, and more. The ergonomic features of this machine reduce operator fatigue while optimizing time and labor savings. The compact design makes it ideal for use in tight spaces.

5280 Specifications

Power Supply	Electric	
Width	17"	43 cm
Height	39"	99 cm
Length	27"	69 cm
Weight	263 lb	119 kg
Removable Weight	37 lb front, 49 lb saddle	16.8 kg front, 22.2 kg saddle
Weight (machine only)	177 lb	80.3 kg
Speed	12-50 ft/min	3.7-15.2 m/min
RPM	1725/1425	
Voltage	115	230
Frequency	60 Hz	110 V / 50 Hz
HP	1	.746 kW
Amps (full load)	12/6.7	
Noise Emission	77 dB	

Meets the requirements of the Machine Directive 2006/42/EC and EMC Directive 2004/108/EC. It is CE marked.

SAFETY

A. Tie-down/lifting bail

COMFORT

B. Forward self-propelled control

PERFORMANCE

C. Variable speed, 12 to 50 feet per minute

D. Self-contained, limited-maintenance hydraulic fluid

E. Removable 49-pound saddle weight helps increase or decrease down pressure and traction

F. Orbital action rotates the cutting blade to cut through a range of materials over various substrates; extends life cycle of machine while reducing maintenance costs

INCLUDED WITH THE 5280

- Kit 5173 includes:
 - 148 5" x 6" blade
 - 6258-BU 3" x 12" self-scoring blade
 - 6286 3" x 10" heavy-duty blade
 - 7050-200 3" x 6" premium high-tempered blade
 - 7050-202 3" x 10" premium high-tempered blade
- 5280-137W: 6 mm t-handle wrench
- Operating and Service Manuals
- One-year manufacturer's warranty on parts and labor

RECOMMENDED ACCESSORIES

6280-505

- Swivel head rotates to allow continuous contact with the floor

6280-500

- Swivel head allows for continuous contact with the floor and is specifically for razor blades