



Husqvarna Soff-Cut 4200

The Husqvarna 4200 self-propelled dry-cutting gasoline saw has a low-noise enclosed design and is ideal for heavy-duty commercial, industrial and paving applications. The 4200 is designed for peak performance. Features include a 23 hp twin-cylinder gasoline engine, three-stage cyclonic air cleaner, oil cooler, full-pressure oil lubrication, hydraulic valve lifters, mechanical fuel pump and oil alert light. Multiple blade widths can be used, allowing different joint widths and crack control simultaneously.

Engine	
Output power (As rated by the engine/motor manufacturer)	23 hp
Starter	Electric

Cutting equipment		
Blade depth control	Electric	
Cutting depth, max	3 in	
Dimensions		
Weight	488 lbs	
Product size length	89 in	
Product size height	40.25 in	

Articles for Soff-Cut 4200

EARLY ENTRY SAWS Soff-Cut 4200 23 hp | 14" | Kohler | Dust Port Cover

966 84 56-04

Features for Soff-Cut 4200

Soff-Cut® technology

Husqvarna Soff-Cut is a unique patented system for early entry concrete sawing. This technology enables concrete to be cut within the first one or two hours of finishing and before final set. Husqvarna Soff-Cut® provides the best solution for minimizing the risk of random cracking, and it simplifies the working process, compared to conventional sawing.



Accessories for Soff-Cut 4200



ELITE SOFF-CUT XL 2000



ELITE SOFF-CUT XL 3000



ELITE SOFF-CUT XL 5000



XL-1000



XL-1000



XL-1000

Check website for more accessories.











XL-1000

ELITE SOFF-CUT XL 2000

ELITE SOFF-CUT XL 3000

XL-4000

ELITE SOFF-CUT XL 5000

Abrasive	\bullet \circ \circ		$\bullet \bullet \bigcirc$	$\bullet \bullet \bigcirc$
Green concrete: Hard aggregate (flint), Non- abrasive sand	• • •			
Green concrete: Medium aggregate (granite), Medium abrasive sand		•••	•••	
Green concrete: Medium to Soft aggregate (Limestone), abrasive sand				•••
Trap-rock	• • •			











XL-6000

VARI-CUT 1000 Purple VARI-CUT 3000 Red

VARI-CUT 4000 Orange

FLX-1000

	i di pic	Nou	orange	
Abrasive		•••	$\bullet \bullet \bigcirc$	
Granite		• 0 0	• • •	
Green concrete: Hard aggregate (flint), Medium abrasive sand	• • 0	•••		••0
Green concrete: Hard aggregate (flint), Non-abrasive sand	• • •	• 0 0		•••
Green concrete: Medium aggregate (granite), Medium abrasive sand	• 0 0	••0	••0	
Green concrete: Medium to Soft aggregate (Limestone), abrasive sand	•		•••	
Trap-rock	• 0 0	• • •		





FLX-4000

Granite	$\bullet \bullet \bigcirc$	•••
Green concrete: Hard aggregate (flint), Medium abrasive sand	•••	
Green concrete: Medium aggregate (granite), Medium abrasive sand	•••	••0
Green concrete: Medium to Soft aggregate (Limestone), abrasive sand	•••	•••