



Husqvarna PG 830 S

PG 830 S grinder focus on core grinding performance. It is a single motor version of the largest floor grinder size in the Husqvarna PG-range. This is a good choice for most grinding jobs, and for users that prefer a non-motorised drive. The PG 830 S is easy to use, still with large capacity thanks to the 32 in / 830 mm grinding width. Adjustable weights for extra grinding pressure are optional. Key components are sealed against dust and slurry for maximised reliability and low maintenance.

Motor		
Rated input power	15 hp	
Rated current	30 A	
Voltage	440-480 V	
Phases	3	
Pins	3P+E	

Other		
Grinding disc diameter	10.5 in	
Direction of rotation	Both directions	
Number of grinding discs	3	
Dimensions		
Product size length	61 in	
Product size width	32.7 in	
Product size height	45.1 in	
Weight	1096 lbs	

Articles for PG 830 S

FLOOR GRINDER PG 830 S 440-480 V | 3-ph | 50-60 Hz | US

FLOOR GRINDER PG 830 S 220-240 V | 3-ph | 50-60 Hz | US

967 97 77-02 967 97 77-04

Features for PG 830 S

Sealed to last

Sealed grinding head with 1000 hrs service interval. No dust or water can intrude to damage components.



Ergonomic handle

Adjustable handle for better ergonomics.



Adjustable grinding pressure

The optional weights are a musthave for every professional grinder, as they allow to adjust the grinding pressure in three pre-set positions. They also make tilting the machine that much easier.



Protected electronics

Dust sealed electrical cabinet with external cooling technology.



Accessories for PG 830 S



Flexible grinding head spring steel replacement



Tool box



Redi Lock® diamond holder disc




Water kit

Check website for more accessories.

Recommended tools for PG 830 S

			and the second s		
	G1410 3 PCS	G1420 3PCS	G1440 3PCS	G1470 3PCS	G1480 3PCS
Concrete hard	$\bullet \bullet \bullet$	$\bullet \bullet \bullet$	$\bullet \circ \circ$		
Concrete medium			$\bullet \bullet \bigcirc$		
Concrete soft				•••	
Paint and thin epoxy	$\bullet \bigcirc \bigcirc$		$\bullet \bullet \bullet$		$\bullet \bigcirc \bigcirc$
Plastic-like ceramic glues			$\bullet \bullet \bullet$		
Porous ceramic glues				$\bullet \bullet \bullet$	
Rain-damaged concrete					$\bullet \bullet \bullet$
Semi-polished concrete	$\bullet \bullet \bullet$				
Thick epoxy	$\bullet \bigcirc \bigcirc$		$\bullet \bullet \bullet$	$\bullet \circ \circ$	
Vinyl glues	$\bullet \bigcirc \bigcirc$	$\bullet \bullet \bigcirc$	$\bullet \bullet \bullet$	$\bullet \bigcirc \bigcirc$	$\bullet \circ \circ$





HiperFlex FT80

Concrete	$\bullet \bullet \bullet$
Concrete medium	
Concrete soft	
Terrazzo	$\bullet \bullet \bullet$

