



Made in America Since 1968

PRO

THE FUTURE OF WALK-BEHIND



FRONT END

Adjustable orbital speed from 0 - 1900 RPMs.

Quick change tooling holder provides transitions with the click of a button.



CONTROLS

Two thumb controls allow responsive, precision steering with very little input from the operator.

A simple toggle infinitely switches blade pitch and angle.



OPERATION

Built-in wheel de-coupler puts your machine into transport mode with no loose parts.

Forward and reverse wheel scrapers.

Front, middle, and side weights are removable and positionable.

This modular machine is designed to be pulled apart and transported with ease.

“What this machine can do will really change the way the game is played.”

RICK | PRESIDENT, BOTTOM ZUPP FLOOR REMOVAL

ROGUE

WOOD SCRAPING



BLADE POSITIONS

3-150
FT/MIN

ROGUE Specifications

Power Supply	Electric	
Max. Width	22.1"	56 cm
Width (weights forward)	19.4"	49 cm
Max. Height	45.3"	115 cm
Height (handle folded)	25.3"	64 cm
Max. Length	56.8"	114 cm
Length (handle folded)	41.4"	105 cm
Weight	466 lbs	211.4 kg
Removable Weight	177 lbs	80.3 kg
Weight (machine only)	289 lbs	131.1 kg
Speed	3 - 150 ft/min	0.9 - 45.7 m/min
RPM	600-2200 RPM	
Voltage	120 V	
Frequency	60 Hz	
HP	Drive Motor - 1/3 hp (x2) Orbital Motor - 3/4 hp	
Amps (full load)	15 A	
Noise Emission		

INCLUDED WITH ROGUE

- **6255-BU**
Self-Scoring Blade
90°, 4" x 6" x .062"
- **7050-200**
Premium High Tempered Blade
3" x 6" x .062"
- **7280-10GV**
10" Cutting Head, Grooved
- **7082-8GV**
Wood Floor Shank
2.5" x 8", Grooved
- **7281-1GV**
Angle Shank w/ Carbide Tip
1" x 6", Grooved

